



PRODUCT DATA SHEET

AGS 2+

Graffiti Remover - For porous surfaces, in warm weather

- AGS 2+ is a powerful graffiti and paint remover
- For use on exterior and interior surfaces
- AGS 2+ may be used on porous surfaces for all weather conditions
- Readily biodegradable according to OECD test 302 b

INSTRUCTIONS FOR USE

Material

Remove graffiti with AGS 2+ when found on the following surfaces:

Porous substrate

Granite, quartz, porphyry, dolomite, surface painted with non-organic paint, treated marble, limestone, slate and concrete.

Hard substrate

Metal, treated wood, clinker, glazed brick and some plasters.

Graffiti-removal

Apply AGS 2+ with a brush or airless sprayer. Agitate the surface well. Leave until graffiti has dissolved, 20 to 60 min. When cold, the time increases. Jet off with hot water and high pressure, (90°C, 150 bar/2175 PSI). Lance nozzle spread should be 15 - 25 degrees and water flow should be 15 to 20 ltrs/minute, (4-5 gal/minute). Note: For metal surfaces do not use to high pressure. Instead wipe with sponge or cloth and rinse with warm water.

Dosage

Use concentrate.

Consumption

0.5 - 1.0 ltr/m².

Guidelines

- Supplied in 5 or 25 ltrs plastic jerry can
- Viscous yellowish fluid.
- Specific weight 1,08 kg/ltr
- Mild odour
- Contains Solvents, surfactants.

Precautions

Protective clothing. Visor when high pressure washing and breathing mask in poorly ventilated areas.

Storage

Store frost-free in original closed container.

Shelf life

Approximately 24 months in unopened container.

Marking



IRRITATING TO EYES AND SKIN

Not classified in ADR or IMDG.

This product information is intended as a guide for use of this product. AGS Australia cannot give any guarantee for end result achieved. Applicator of product should carry out testing and be responsible for the result

AGS Anti Graffiti Systems Australia
(Rear) 3 Queens Road, Hurstville, NSW 2220
Ph: 9586 4555 Fax: 9586 1966