

PRODUCT INFORMATION

Manufacturer's code: RPNMG
10/10/2005

Updated:

Product Name: NO MORE GRAFFITI

Description: NO MORE GRAFFITI is a sacrificial anti-graffiti coating based on aqueous wax polymer emulsions. Once applied to a surface. NO MORE GRAFFITI forms a thin film between the surface to be protected and any graffiti or other staining substance. The graffiti can be easily removed by simply cleaning the surface with hot, high-pressure water. The removal process strips the film of NO MORE GRAFFITI together with the graffiti resulting in a clean, stain-free surface.

The non-stick nature of surfaces treated with NO MORE GRAFFITI may also discourages the adhesion of glue-on advertising posters.

Recommended Uses: NO MORE GRAFFITI is used as a low cost sacrificial anti-graffiti measure on all types of masonry surfaces such as brick, concrete, and blockwork. It is NOT designed for timber, painted surfaces or surface coated with textured coating or polymer render.

Some of outstanding features of NO MORE GRAFFITI include:

- Good resistance to graffiti.
- UV stable emulsion composition.
- The product and method of removal are environmentally friendly, no organic solvents, i.e. paint strippers, are required.
- Easy application by brush, roller or airless spray.
- Non corrosive and non flammable, all equipment can be cleaned in water.

As building materials varies, it is strongly recommended that a test MUST be carried out prior to application to find out the suitability of this product for the purposes.

Use Instructions: Application

1. The surface to be treated should be dry, firm, and clean free from oil and friable laitance. Otherwise, surface should be washed and allowed to dry before application.
2. If the substrate surface is too porous, it is strongly recommended to pre-seal the surface before using this product by using an appropriate sealer.
3. Do not apply if rain is expected or if conditions are damp and temperature is below 10°C or if under excessively hot and windy conditions.
4. The product can be applied brush, roller or airless spray. Drying times depend on climatic conditions typical drying times are in the order of 2 hours.
5. The consumption of coats depends on the porosity of the surface being coated. Smooth off-form concrete generally requires only 1 coat and has a consumption rate of approximately 10m²/litre. However, porous substrates may require 2 or more coats for maximum effectiveness.
6. Product is water-based and therefore clean up all equipment in water.

Removal instructions:

Washing with a stream of hot water can clean the area that has been subjected to graffiti. The hot water should exit the pressure nozzle in the form of a fan at a pressure of 500-1000 psi. The temperature should be preferably above 90°C.

Re-application of NO MORE GRAFFITI can be performed once the surface is dry.

Typical Data:	Appearance:	Yellowish viscose emulsion with slight odour
	Solids content:	<50% by weight
	Specific gravity:	1.0
	pH value:	7-9
	Solubility in water:	Miscible
	Flash point:	>100°C

Important Note: As products and the conditions of use vary, it is strongly recommended that a pilot trial **MUST** be carried out prior to using NO MORE GRAFFITI to determine the suitability of this product for the purpose.

Handling & Storage: NO MORE GRAFFITI is a non-flammable, non-corrosive and non-toxic water-based product. However, as with all chemical products, good industrial hygiene procedures should be used when using this product. Skin and eye contact should be avoided by using suitable protective measures such as chemically resistant gloves and goggles. Wash all spills with plenty of water. Refer to the material safety data sheet if accidentally swallowed or splashed into eyes.

Keep out of reach of children.

NO MORE GRAFFITI can be stored in closed plastic containers for 12 months. The product should be protected from freezing. Prolonged temperatures greater than 35°C must be avoided.

This product should not be used past its use-by date printed on the label. However, if the product is passed its use-by-date, it is not necessarily unusable. A quality control should be performed on the properties relevant to the application or otherwise contact the manufacturer for further advice.

Packaging: NO MORE GRAFFITI is available in 5, 10 and 20 plastic drums. Other size containers may be available on request.

Anti-Graffiti Systems
ABN 81 002 905 188
3 Queens Road
HURSTVILLE NSW 2220
Australia

Tel: +61(2) 9586 4555
Fax: +61(2) 9586 1966
office@antigrffiti.com.au

Disclaimer:

The information given in this data sheet is based on many years of experience and is correct to the best of our knowledge. As the storage, handling and application of this material are beyond our control; we can only be responsible for the quality of our product at the time of dispatch. We reserve the right to alter certain product parameters within the spectrum of properties in order to keep abreast of technical advances. It is the responsibility of the end user to determine the suitability of this material for any particular application.